

Specification of document Delivery schedule (DELFOR) in XML – EDInet (Ver 1.3)



Authors:	Project team Infinite
Version/ Date of publication:	Ver 1.3 / 07.09.2017
Copyrights: 	INFINITE Sp. z o.o. www.infinite.pl www.edinet-solutions.com

Field name	Type	Format	Description
<Delfor>	M		
<DelforHeader>	M		
<DelforNumber>12345</DelforNumber>	M	AN(50)	Delivery schedule document number
<DelforNumberOld>12345</DelforNumberOld>	O	AN(50)	Previous delivery schedule document number
<DelforDate>2012-03-20</DelforDate>	M	YYYY-MM-DD	Date of delivery schedule document
<DeliveryDateFrom>2012-03-20</DeliveryDateFrom>	O	YYYY-MM-DD	Delivery date, earliest
<DeliveryDateTo>2012-03-28</DeliveryDateTo>	O	YYYY-MM-DD	Delivery date, latest
<ForecastPeriodFrom>2012-03-20</ForecastPeriodFrom>	O	YYYY-MM-DD	Forecast period date from
<ForecastPeriodTo>2012-03-28</ForecastPeriodTo>	O	YYYY-MM-DD	Forecast period date to
<Comment></Comment>	O	AN(4000)	Comment
<DocumentPurposeCode>F</DocumentPurposeCode>	M	AN(3)	F - Delivery forecast; S - Product delivery schedule; R - Product schedule response;
<DocumentRoleCode>A</DocumentRoleCode>	O	AN(3)	A - addition, D - removal, M - modification
<CumulativeReceivedQtyResetDate></CumulativeReceivedQtyResetDate>	O	YYYY-MM-DD	Date of resetting the cumulative quantity received
<ReferenceDocs>	O		Reference documents - associated with DELFOR
<OrderAtBuyer>	O		Order in the buyer system
<DocID>123123</DocID>	M	AN(50)	Document number
<DocDate>2012-01-20</DocDate>	O	YYYY-MM-DD	Document date
</OrderAtBuyer>			
<OrderAtSeller>	O		Order in the seller system
<DocID>123123</DocID>	M	AN(50)	Document number
<DocDate>2012-01-20</DocDate>	O	YYYY-MM-DD	Document date
</OrderAtSeller>			
<DeliveryDocument>	O		Delivery note
<DocID>123123</DocID>	M	AN(50)	Document number
<DocDate>2012-01-20</DocDate>	O	YYYY-MM-DD	Document date
</DeliveryDocument>			
</ReferenceDocs>			

Field name	Type	Format	Description
</DelforHeader>			
<DelforParty>	M		
<BuyerParty>	M		Communication party – Buyer
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</BuyerParty>			
<ShipToParty>	M		Communication party – Delivery location
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</ShipToParty>			
<SellerParty>	M		Communication party – Seller
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</SellerParty>			
<ShipFromParty>	O		Communication party – Shipping location
<Name></Name>	M	AN(500)	Nazwa strony uczestniczącej w komunikacji
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</ShipFromParty>			
<ForwarderParty>	O		Communication party – Forwarder
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</ForwarderParty>			
<ConsigneeParty>	O		Communication party – Recipient
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</ConsigneeParty>			
</DelforParty>			
<DelforDetail>	M		

Field name	Type	Format	Description
<Item>	M(*)		
<ItemNum>1</ItemNum>	M	INT	Position number in the document
<ActionCode>3</ActionCode>	O	AN(3)	Code of required action on a particular position: 3 = change; 4 = without change ; 5 = accepted; 6 = accepted with corrections; 7 = not accepted
<EAN>4487674421091</EAN>	O	AN(50)	European Article Number
<UPC></UPC>	O	AN(50)	Universal Product Code
<BuyerItemID>123ABC</BuyerItemID>	O	AN(50)	Buyer's article number
<SellerItemID>123ABC</SellerItemID>	O	AN(50)	Supplier's article number
<Name>ABCABC</Name>	O	AN(50)	Product name
<Description></Description>	O	AN(2000)	Item description
<Comment></Comment>	O	AN(4000)	Item comment
<QuantityValue>10.00</QuantityValue>	O	DEC(12,3)	Quantity
<UnitOfMeasure>PCE</UnitOfMeasure>	O	AN(3)	Unit of measure code
<DeliverySchedule>	O		Delivery schedule details
<CallOff>	O		Delivery cancellation details
<DocID>54321</DocID>	O	AN(500)	Delivery cancellation number
<DocDate>2012-03-03</DocDate>	O	YYYY-MM-DD	Delivery cancellation date
</CallOff>			
<CallOffOld>	O		Details of previous delivery cancellation document
<DocID>54221</DocID>	O	AN(500)	Previous delivery cancellation document number
<DocDate>2012-02-02</DocDate>	O	YYYY-MM-DD	Previous delivery cancellation date
</CallOffOld>			
<DeliveryRequirementCode></DeliveryRequirementCode>	O	AN(50)	Shipping Requirements: DA = Do not deliver after; DB = Do not deliver before; DD = Delivery on; P2 = Deliver as soon as possible; SC = Delivery full order.
<FrequencyCode></FrequencyCode>	O	AN(50)	Delivery frequency: M = monthly; Q = quarterly; W = weekly; Y = daily; D - specific date

Field name	Type	Format	Description
<DespatchPatternCode>117</DespatchPatternCode>	O	AN(50)	Specific delivery date indication (EDIFACT - position 2015). E.g .: 1 - first week of the month; 17 - Friday
<ScheduleDetails>	O		Details of a particular schedule
<Item>	M(*)		Item details
<QuantityValue>8.00</QuantityValue>	O	DEC(12,3)	Quantity despatched/sent
<UnitOfMeasure>PCE</UnitOfMeasure>	O	AN(3)	Unit of measure code
<RequestedDeliveryDate></RequestedDeliveryDate>	O	YYYY-MM-DD	Requested delivery date
<PlanedDeliveryDate></PlanedDeliveryDate>	O	YYYY-MM-DD	Planed delivery date
</Item>			
</ScheduleDetails>			
</DeliverySchedule>			
<Package>	O		Package details
<PackageQuantity></PackageQuantity>	O	DEC(12,3)	The number of packages
<PackageContentQty></PackageContentQty>	O	DEC(12,3)	Quantity in particular package
<PackageContentUnitOfMeasure></PackageContentUnitOfMeasure>	O	AN(50)	Unit of measure for quantity in the particular package
<PackageTypeCode></PackageTypeCode>	O	AN(50)	Package type code
<BuyerPackageID></BuyerPackageID>	O	AN(50)	Buyer's package code
<SellerPackageID></SellerPackageID>	O	AN(50)	Supplier's package code
</Package>			
<PacketContentQuantity></PacketContentQuantity>	O	DEC(12,3)	Number of sales unit in package (pc in box
<LastDeliveryDate>2012-02-02</LastDeliveryDate>	O	YYYY-MM-DD	Date of last delivery
<LastDeliveryQuantity></LastDeliveryQuantity>	O	DEC(12,3)	Quantity of last delivery
<LastDeliveryUOM></LastDeliveryUOM>	O	AN(3)	Unit of measure for the quantity of last delivery
<CumulativeReceivedQty>20.00</CumulativeReceivedQty>	O	DEC(12,3)	Cumulative quantity received
<ArrearsQty>20.00</ArrearsQty>	O	DEC(12,3)	Overdue quantity
<ImmediateRequirementQty>5.00</ImmediateRequirementQty>	O	DEC(12,3)	Quantity required for immediate delivery
<DelforParty>	O		
<ShipToParty>	O		Communication Parties to which goods should be delivered

Field name	Type	Format	Description
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</ShipToParty>			
<ShipFromParty>	O		Communication Parties from which goods should be delivered
<Name></Name>	M	AN(500)	The name of the communicating party
<ILN></ILN>	M	AN(50)	International Location Number/ Global Location Number
</ShipFromParty>			
</DelforParty>			
<ReferenceDocs>	O		Reference documents – associated with DELFOR
<OrderAtBuyer>	O		Order in the buyer system
<DocID>123123</DocID>	M	AN(50)	Document number
<DocDate>2012-01-20</DocDate>	O	YYYY-MM-DD	Document date
</OrderAtBuyer>			
<OrderAtSeller>	O		Order in the seller system
<DocID>123123</DocID>	M	AN(50)	Document number
<DocDate>2012-01-20</DocDate>	O	YYYY-MM-DD	Document date
</OrderAtSeller>			
<DeliveryDocument>	O		Delivery note
<DocID>123123</DocID>	M	AN(50)	Document number
<DocDate>2012-01-20</DocDate>	O	YYYY-MM-DD	Document date
</DeliveryDocument>			
</ReferenceDocs>			
</Item>			
</DelforDetail>			
</Delfor>			

O* – Optional field, segment may occur repeatedly

R(X)	Real number with precision to the x position of the decimal point separator „.” dot
------	---

other	Eancom compatible
-------	-------------------

2/ Fields: order number, order date, delivery number, date of document delivery, place of delivery can be transmitted on the lines or in the header. The principle of transfer in / data in the header for the case where all goods sold refers to the same order number, order date, delivery number, date, document delivery and place of delivery.